

PUBLIC WORKS DEPARTMENT ENGINEERING DIVISION

411 Main Street, 2nd Floor P.O. Box 3420 Phone: (530) 879-6900 Fax: (530) 895-4899 Chico, CA 95927-3420 www.ci.chico.ca.us

DEVELOPMENT ENGINEERING DESIGN BULLETIN

CATEGORY: 3 Improvement Plans, General

TITLE: 3.1.2 Construction Notes

DATE: **August 5, 2008**

THE FOLLOWING IS A LIST OF ITEMS THAT MAY APPLY TO IMPROVEMENT PLANS AND WILL BE REQUIRED WITHIN THE CONSTRUCTION NOTES OR FOR IMPLEMENTATION INTO THE IMPROVEMENT PLANS:

- 1. A 10-foot conforming grind will be required for new pavement sections that transition into existing pavement. The requirement applies to areas where the new street ties into a recently constructed or reconstructed roadway.
- 2. All paving shall be installed per current Caltrans Standards Specifications Section 39: Asphalt Concrete.
- 3. For all improvement plans, AC shall be described as HMA defined as type "B" hot mix asphalt $-\frac{3}{4}$ " maximum, medium grade.
- 4. Stop signs to be installed shall be 30" and shall meet the California M.U.T.C.D. Supplement Requirements.
- 5. Contractors shall call the City of Chico municipal service center general phone number (530) 894-4200 at least 72 hours in advance of starting work to allow the marking of the location of city owned facilities. For all other utilities, call the USA North hotline at 1-800-227-2600 a minimum of 48 hours prior to excavation.
- 6. A traffic control plan shall be required and shall be submitted by the contractor to the City Construction Inspector when working in the City of Chico streets.
- 7. The Contractor shall submit a shoring and sheeting plan to the City Construction Inspector when excavating deeper than 5 feet and when sloping is not able to meet O.S.H.A. requirements.